



2025

SECTION 9 - Bombers

1. Driver Eligibility:

- 1.1. Must be at least 18 years of age or demonstrate ability.
- 1.2. Final decision is subject to track approval

2. Eligible Cars:

- 2.1. Any 6- or 8-cylinder car with a complete stock engine, body, frame and suspension for that year, make and model.
- 2.2. NO rotary engines. NO mid-engine or turbo cars are allowed.
- 2.3. NO 4-wheel, all-wheel, or front wheel drive cars are allowed.
- 2.4. NO mid or rear engine cars are allowed.

3. MINIMUM SAFETY & PPE

- 3.1. PERSONAL PROTECTIVE GEAR, see SECTION 5 - MINIMUM EQUIPMENT AND SPECS
- 3.2. ROLL CAGE - 4-point cage allowed, roll bar required, see SECTION 5 - MINIMUM EQUIPMENT AND SPECS
- 3.3. Other minimum Specs, see SECTION 5 - MINIMUM EQUIPMENT AND SPECS

4. Car Specifications:

- 4.1. Cars must remain factory stock; No modifications, alterations, or additions allowed unless specifically stated within these rules
- 4.2. Computer settings must remain factory stock.
- 4.3. Quick release steering wheels are highly recommended.
- 4.4. If stock gas tank is forward of rear axle, it may remain in place.
 - 4.4.1. The tank must have two fronts to rear straps on top and around bottom of tank.
 - 4.4.2. One side to side strap is required in the same fashion as the front to rear straps.
- 4.5. If stock gas tank is behind rear axle, it must be replaced with a commercially produced fuel cell. see SECTION 5 - MINIMUM EQUIPMENT AND SPECS
- 4.6. Frame
 - 4.6.1. No modifications, alterations, or additions allowed unless specifically stated within these rules
 - 4.6.2. Complete bumper to bumper steel frame and unit-body must be retained. NO lightning permitted
- 4.7. Bodies
 - 4.7.1. Cars must retain their stock appearance, no cutting, chopping, channeling, or shortening permitted.



- 4.7.2. All stock steel unaltered floor pans, firewalls, trunk compartment, wheel wells must be retained.
- 4.7.3. Complete hood and trunk lids are required.
- 4.7.4. All air bag sensors must be removed.
- 4.7.5. All OEM body parts must remain intact.
- 4.7.6. NO aftermarket body panels are allowed.
- 4.7.7. Aftermarket bumper covers are allowed.
- 4.7.8. All doors must be welded, bolted, or chained shut.
 - 4.7.8.1. Under NO circumstances are driver doors allowed to open and close.
 - 4.7.8.2. Driver's door plate or grater blade is required.
 - 4.7.8.3. Removal of window assembly is allowed.
- 4.7.9. Front & rear bumpers are required.
 - 4.7.9.1. Bumper ends must not exceed body width and must be strapped with 3" x 1/8" steel strap to the fender on front and rear of the car regardless if exposed or covered.
 - 4.7.9.2. Blunt or sharp ends will not be allowed.
- 4.7.10. Hoods
 - 4.7.10.1. Replace stock hood latch with a minimum of 2 pins.
 - 4.7.10.2. Remove all under-hood insulation.
 - 4.7.10.3. Removal of hood bracing is recommended.
 - 4.7.10.4. Stock hinges must remain and the bracing for hinges must remain and a minimum of 2 pins are required.

5. ENGINE and DRIVE-TRAIN SPECIFICATIONS

- 5.1. Engine
 - 5.1.1. Engine must be stock for the make and model and in the original motor mounts
- 5.2. Transmission and Drivetrain
 - 5.2.1. Stock transmission and stock unaltered rear end for that year, make and model required.
 - 5.2.2. 1" inspection hole is required in bellhousing or dust cover to check fly wheel.
 - 5.2.3. RWD cars must have 2 driveline hoops. Must be made from a minimum 2" x 3/16" strap.
 - 5.2.3.1. Rear hoop must be a full circle hoop
 - 5.2.4. Driveline must be painted white with car number on it in a contrasting color.

6. Fuel Delivery

- 6.1. Computer settings must remain factory stock.
- 6.2. Stock carburetor/fuel injection system for that year, make and model required.



- 6.2.1. Two throttle return springs required.
- 6.2.2. No aftermarket metering blocks.
- 6.2.3. Changing of squirters, jets and power valves is allowed.
- 6.2.4. Removal of choke plant is mandatory.
- 6.2.5. Air cleaner required.
- 6.2.6. Gasoline or E85 pump fuel only. NO alcohol, methanol or race fuel is allowed.
- 6.2.7. Electric fuel pumps are allowed.
- 6.2.8. Must be wired to shut off with the master switch.
- 6.2.9. If mounted in the rear area, pump must be protected by a skid plate.
- 6.2.10. Must be equipped with an oil pressure shut off override or inertia switch.
- 7. Suspension**
 - 7.1. No modifications, alterations, or additions allowed
- 8. Car Weight**
 - 8.1. Added or removable ballast weight is NOT permitted.
 - 8.2. No lightning is permitted.
- 9. Radiator and Cooling**
 - 9.1. Radiator must be mounted in stock location.
 - 9.2. Must have 1 gallon metal or made for racing plastic overflow container. (NO plastic drink bottles, milk jugs, car radiator overflow container, etc.)
 - 9.3. Radiator protection is allowed.
 - 9.3.1. Must be made of 1" square tubing, not to exceed 2" past radiator on all sides.
 - 9.4. Fans must have a fan shroud.
 - 9.5. Electric cooling fans are allowed.
- 10. Brakes**
 - 10.1. Must have at least 3 working brakes.
 - 10.2. All brake components must remain in stock location.
 - 10.3. Only 1 master cylinder is allowed
 - 10.4. NO adjustable brake proportioning valves or shut off devices.
 - 10.5. Emergency brake cable must be cut or removed. Subject of track approval.
- 11. Battery and Electrical**
 - 11.1. It is recommended that the battery remains under the hood in stock location
 - 11.2. see SECTION 5 - MINIMUM EQUIPMENT AND SPECS

All modifications are subject to track approval